

# **LONGMAX**

2018 PRODUCT CATALOGUE

## **QINGDAO LONGMAX TYRE CO.,LTD**

- Add: 7F,NO.288 Shuangzhu Road, West Coast District,Qingdao, China
- Tel: 0086-532-55588070
- Email: sales@longmaxtyre.com
- Fax: 0086-532-55588060
- Http:www.longmaxtyre.com



**QINGDAO LONGMAX TYRE CO.,LTD**

# PRODUCT CATALOGUE

**LONG HAUL PAGE 04**



**LONG HAUL PAGE 06**



**LONG HAUL PAGE 08**



**LONG HAUL PAGE 10**



**REGIONAL PAGE 13**



**LONG HAUL PAGE 05**



**LONG HAUL PAGE 07**



**LONG HAUL PAGE 09**



**REGIONAL PAGE 12**



**REGIONAL PAGE 14**



**REGIONAL PAGE 17**



**REGIONAL PAGE 19**



**REGIONAL PAGE 21**



**REGIONAL ON/OFF ROAD PAGE 23**



**REGIONAL ON/OFF ROAD PAGE 25**



**REGIONAL PAGE 15**



**REGIONAL PAGE 18**



**REGIONAL PAGE 20**



**REGIONAL PAGE 22**



**REGIONAL ON/OFF ROAD PAGE 24**



**REGIONAL ON/OFF ROAD PAGE 26**



# LONG HAUL PRODUCT DISPLAY

# 01



## PATTERN LMT11

| SIZE     | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|          |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 8.25R16  | 18 | 131/126       | L            | 6.50H        | 14.0             | 230                | 858               | 1950          | 1700 | 770                | 770  |
| 9.5R17.5 | 18 | 143/141       | K            | 6.75         | 14.5             | 236                | 843               | 2725          | 2575 | 860                | 860  |



## PATTERN LMT21

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 315/80R22.5 | 20 | 157/154       | L            | 9.00         | 16.5             | 320                | 1080              | 4125          | 3750 | 900                | 900  |
| 12R22.5     | 18 | 152/149       | L            | 9.00         | 16.5             | 304                | 1081              | 3552          | 3250 | 930                | 930  |
| 9.5R17.5    | 18 | 143/141       | K            | 6.75         | 14.5             | 236                | 843               | 2725          | 2575 | 860                | 860  |



## PATTERN LMT31

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | K            | 9.00         | 16.5             | 300                | 1085              | 3550          | 3250 | 930                | 930  |



## PATTERN LMT41

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 295/80R22.5 | 18 | 152/149       | M            | 9.00         | 14.8             | 293                | 1042             | 3550          | 3250 | 900                | 900  |



## PATTERN LMT71

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 11R22.5     | 16 | 146/143       | M            | 8.25         | 16.5             | 279                | 1054             | 3000          | 2725 | 830                | 830  |
| 295/80R22.5 | 18 | 152/149       | L            | 9.00         | 16.5             | 298                | 1044             | 3550          | 3250 | 900                | 900  |
| 315/80R22.5 | 18 | 154/151       | L            | 9.00         | 16.5             | 312                | 1076             | 3750          | 3450 | 830                | 830  |



## PATTERN LMT51

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | L            | 9.00         | 16.5             | 300                | 1085             | 3550          | 3250 | 930                | 930  |



## PATTERN LMT81

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | L            | 9.00         | 16.5             | 300                | 1085             | 3550          | 3250 | 930                | 930  |



## PATTERN LMT61

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 6.50R16 | 12 | 110/105       | L            | 5.50F        | 10.5             | 185                | 750              | 1060          | 925  | 670                | 670  |
| 7.00R16 | 14 | 111/107       | L            | 5.50F        | 11.0             | 200                | 775              | 1090          | 975  | 560                | 560  |
| 7.50R16 | 14 | 118/114       | L            | 5.50F        | 11.0             | 200                | 775              | 1320          | 1180 | 770                | 770  |
| 8.25R16 | 16 | 128/124       | L            | 6.50F        | 14.5             | 235                | 855              | 1800          | 1600 | 770                | 770  |



## PATTERN LMT747

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 11R22.5     | 16 | 146/143       | M            | 8.25         | 14.5             | 278                | 1054             | 3000          | 2725 | 830                | 830  |
| 315/80R22.5 | 20 | 161/154       | J            | 9.00         | 16.5             | 312                | 1076             | 4625          | 3750 | 900                | 900  |



## PATTERN LMT53

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5     | 18 | 152/149       | L            | 9.00         | 15.5             | 300                | 1085              | 3550          | 3250 | 930                | 930  |
| 315/80R22.5 | 20 | 157/154       | K            | 9.00         | 15.5             | 317                | 1082              | 4125          | 3750 | 900                | 900  |



## PATTERN LMT198

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 7.50R16 | 14 | 122/118       | L            | 6.00G        | 12.0             | 215                | 805               | 1500          | 1320 | 770                | 770  |
| 8.25R16 | 14 | 126/122       | L            | 6.50H        | 12.0             | 235                | 855               | 1700          | 1500 | 670                | 670  |



## PATTERN LMT63

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | L            | 9.00         | 15.5             | 234                | 1085              | 3550          | 3250 | 930                | 930  |



## PATTERN LMT266

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 11R22.5     | 16 | 146/143       | L            | 8.25         | 14.5             | 279                | 1051              | 3000          | 2725 | 830                | 830  |
| 12R22.5     | 18 | 152/149       | L            | 9.00         | 16.5             | 300                | 1085              | 3550          | 3250 | 930                | 930  |
| 295/80R22.5 | 18 | 150/147       | M            | 9.00         | 16.5             | 298                | 1044              | 3350          | 3075 | 830                | 830  |



## PATTERN LMT73

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | L            | 9.00         | 15.5             | 234                | 1085              | 3550          | 3250 | 930                | 930  |



## PATTERN LMT120

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 215/75R17.5 | 14 | 125/122       | M            | 6.00         | 12.5             | 211                | 767               | 1650          | 1500 | 760                | 760  |
| 215/75R17.5 | 16 | 135/133       | L            | 6.00         | 12.5             | 211                | 767               | 1750          | 1600 | 830                | 830  |



## PATTERN LMT816

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 215/75R17.5 | 16 | 135/133       | J            | 6.00         | 13.5             | 226                | 783              | 2180          | 2060 | 850                | 850  |
| 235/75R17.5 | 16 | 143/141       | L            | 6.75         | 13.0             | 233                | 797              | 2725          | 2575 | 860                | 860  |
| 245/70R19.5 | 18 | 135/133       | M            | 7.50         | 14.5             | 248                | 839              | 2180          | 2060 | 830                | 830  |
| 255/70R22.5 | 16 | 140/137       | M            | 7.50         | 14.5             | 257                | 938              | 2500          | 2300 | 830                | 830  |
| 315/70R22.5 | 18 | 152/148       | M            | 9.00         | 15.7             | 299                | 1018             | 3550          | 2150 | 850                | 850  |
| 385/55R22.5 | 20 | 160           | M            | 12.25        | 15.7             | 379                | 1001             | 4500          | —    | 900                | —    |
| 385/65R22.5 | 20 | 160           | K            | 11.75        | 15.7             | 382                | 1076             | 4500          | —    | 900                | —    |



## PATTERN LMT23

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | L            | 9.00         | 14.9             | 300                | 1085             | 3550          | 3250 | 930                | 930  |



## PATTERN LMT33

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 295/60R22.5 | 18 | 150/147       | K            | 9.00         | 14.5             | 292                | 926              | 3550          | 3075 | 900                | 900  |



## PATTERN LMT220

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | L            | 9.00         | 15.0             | 300                | 1085             | 3550          | 3250 | 930                | 930  |



## PATTERN LMT91

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 385/65R22.5 | 20 | 160           | L            | 11.75        | 11.5             | 379                | 1077             | 4250          | —    | 900                | —    |



## PATTERN LMT13

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 385/65R22.5 | 20 | 160           | L            | 11.75        | 14.5             | 386                | 1074             | 4250          | —    | 900                | —    |



## PATTERN LMT200

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 385/65R22.5 | 20 | 160           | J            | 11.75        | 15.5             | 389                | 1072             | 4250          | —    | 900                | —    |

# REGIONAL PRODUCT DISPLAY

# 02



## PATTERN

### LMT10

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 11R22.5     | 16 | 148/145       | K            | 8.25         | 18.0             | 279                | 1060             | 3150          | 2900 | 850                | 850  |
| 12R22.5     | 18 | 152/149       | J            | 9.00         | 19.0             | 305                | 1085             | 3550          | 3250 | 930                | 930  |
| 295/80R22.5 | 18 | 152/149       | K            | 9.00         | 17.0             | 298                | 1044             | 3550          | 3250 | 900                | 900  |
| 315/80R22.5 | 20 | 157/154       | K            | 9.00         | 18.5             | 312                | 1090             | 4125          | 3750 | 900                | 900  |



## PATTERN

### LMT20

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 7.00R16     | 14 | 118/114       | L            | 5.50F        | 11.5             | 200                | 775              | 1320          | 1180 | 770                | 770  |
| 7.50R16     | 14 | 122/118       | L            | 6.00G        | 15.0             | 215                | 805              | 1500          | 1320 | 770                | 770  |
| 8.25R16     | 14 | 126/122       | L            | 6.50H        | 15.5             | 235                | 855              | 1700          | 1500 | 670                | 670  |
| 12.00R20    | 18 | 154/151       | K            | 8.50         | 17.0             | 315                | 1125             | 3750          | 3450 | 830                | 830  |
| 11R22.5     | 16 | 146/143       | M            | 8.25         | 16.5             | 179                | 1054             | 3000          | 2725 | 830                | 830  |
| 12R22.5     | 18 | 152/149       | K            | 9.00         | 16.0             | 234                | 1085             | 3550          | 3250 | 930                | 930  |
| 315/80R22.5 | 18 | 154/151       | M            | 9.00         | 17.0             | 312                | 1082             | 3750          | 3450 | 830                | 830  |



## PATTERN

### LMT30

| SIZE     | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|          |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 11R22.5  | 16 | 146/143       | K            | 8.25         | 17.5             | 279                | 1054             | 3000          | 2725 | 830                | 830  |
| 12.00R20 | 18 | 154/151       | K            | 8.50         | 16.0             | 315                | 1125             | 3750          | 3450 | 830                | 830  |
| 12R22.5  | 18 | 152/149       | K            | 9.00         | 18.5             | 300                | 1085             | 3550          | 3250 | 930                | 930  |
| 13R22.5  | 18 | 154/151       | K            | 9.75         | 19.5             | 320                | 1124             | 3750          | 3450 | 830                | 830  |



**PATTERN**  
**LMT40**

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | L            | 9.00         | 15.8             | 290                | 1082             | 3550          | 3250 | 930                | 930  |



**PATTERN**  
**LMT70**

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | L            | 9.00         | 15.5             | 300                | 1085             | 3550          | 3250 | 930                | 930  |



**PATTERN**  
**LMT50**

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | K            | 9.00         | 18.0             | 290                | 1085             | 3550          | 3250 | 930                | 930  |



**PATTERN**  
**CG20**

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 265/70R19.5 | 16 | 140/138       | J            | 7.50         | 17.5             | 268                | 879              | 2725          | 2575 | 850                | 850  |
| 275/70R22.5 | 16 | 148/145       | K            | 8.25         | 20.0             | 278                | 960              | 2800          | 2575 | 830                | 830  |
| 295/80R22.5 | 18 | 152/149       | K            | 9.00         | 20.0             | 300                | 1053             | 3550          | 3250 | 900                | 900  |
| 11R22.5     | 16 | 148/145       | K            | 8.25         | 20.0             | 282                | 1064             | 3000          | 2725 | 830                | 830  |



**PATTERN**  
**LMT60**

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | L            | 9.00         | 15.5             | 300                | 1085             | 3550          | 3250 | 930                | 930  |



**PATTERN**  
**LMT518**

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERAL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                  | SINGLE        | DUAL | SINGLE             | DUAL |
| 295/80R22.5 | 18 | 152/149       | K            | 9.00         | 16.5             | 298                | 1044             | 3550          | 3250 | 900                | 900  |





**REGIONAL**  
PRODUCT DISPLAY

03



**PATTERN**  
**LMT210**

| SIZE           | PR      | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------------|---------|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|                |         |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 265/70R19.5 16 | 143/141 | J             | 7.50         | 17.3         | 262              | 867                | 2725              | 2575          | 850  | 850                |      |



**PATTERN**  
**LMT910**

| SIZE           | PR      | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------------|---------|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|                |         |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 9R22.5         | 14      | 136/134       | J            | 6.75         | 15.5             | 229                | 974               | 2240          | 2120 | 830                | 830  |
| 10R22.5        | 16      | 144/142       | J            | 7.50         | 18.0             | 254                | 1019              | 2800          | 2650 | 900                | 900  |
| 275/70R22.5 16 | 144/141 | J             | 8.25         | 18.5         | 276              | 958                | 2800              | 2575          | 830  | 830                |      |



**PATTERN**  
**LMT02**

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 295/80R22.5 | 18 | 152/149       | L            | 9.00         | 22.5             | 296                | 1055              | 3550          | 3250 | 900                | 900  |



**PATTERN**  
**LMT288**

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 315/80R22.5 | 20 | 161/154       | G            | 9.00         | 22               | 312                | 1082              | 4625          | 3750 | 900                | 900  |
| 11R22.5     | 16 | 146/143       | L            | 8.25         | 19               | 278                | 1065              | 3000          | 2725 | 830                | 830  |
| 235/75R17.5 | 16 | 132/129       | M            | 6.75         | 14.5             | 233                | 797               | 2000          | 1875 | 830                | 830  |
| 295/80R22.5 | 18 | 152/149       | L            | 9.00         | 22               | 296                | 1050              | 3550          | 3250 | 900                | 900  |



**PATTERN**  
**LMT06**

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 315/80R22.5 | 20 | 157/154       | K            | 9.00         | 23.5             | 313                | 1098              | 4125          | 3750 | 900                | 900  |

WIDER TREAD



**PATTERN**  
**LMT268**

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 315/80R22.5 | 20 | 161/154       | G            | 9.00         | 22               | 312                | 1076              | 4625          | 3750 | 900                | 900  |
| 12R22.5     | 18 | 152/148       | L            | 9.00         | 23               | 300                | 1096              | 3550          | 3150 | 850                | 850  |



**PATTERN**  
**LMT22**

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | K            | 9.00         | 23               | 304                | 1102              | 3550          | 3250 | 930                | 930  |



**PATTERN**  
**LMT568**

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | L            | 9.00         | 14.5             | 300                | 1085              | 3550          | 3250 | 930                | 930  |



**PATTERN**  
**LMT310**

| SIZE           | PR      | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------------|---------|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|                |         |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 215/75R17.5 14 | 126/124 | M             | 6.00         | 15           | 212              | 767                | 1700              | 1600          | 700  | 700                |      |
| 215/75R17.5 16 | 135/133 | L             | 6.00         | 15           | 212              | 767                | 2180              | 2060          | 850  | 850                |      |



**PATTERN**  
**LMT677**

| SIZE     | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|          |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 8.25R16  | 18 | 131/126       | K            | 6.50         | 16.5             | 230                | 863               | 1950          | 1700 | 830                | 830  |
| 9.5R17.5 | 18 | 143/141       | J            | 6.75         | 16.5             | 236                | 843               | 2725          | 2575 | 860                | 860  |
| 11R22.5  | 16 | 148/145       | K            | 8.25         | 23.5             | 279                | 1071              | 3150          | 2900 | 850                | 850  |
| 12R22.5  | 18 | 152/149       | J            | 9.00         | 25.5             | 298                | 1099              | 3550          | 3250 | 930                | 930  |



**PATTERN**  
**LMT588**

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5     | 18 | 152/149       | K            | 9.00         | 21               | 300                | 1085              | 3550          | 3250 | 930                | 930  |
| 315/80R22.5 | 18 | 154/151       | K            | 9.00         | 21.5             | 312                | 1082              | 3750          | 3450 | 830                | 830  |



**PATTERN**  
**LMT32**

| SIZE     | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|          |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 9.5R17.5 | 18 | 143/141       | J            | 6.75         | 18               | 246                | 842.5             | 2725          | 2575 | 860                | 860  |



**PATTERN**  
**LMT579**

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | L            | 9.00         | 22               | 300                | 1096              | 3550          | 3250 | 930                | 930  |



**PATTERN**  
**LMT12**

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 11R22.5     | 16 | 146/143       | K            | 8.25         | 23               | 279                | 1065              | 3000          | 2725 | 830                | 830  |
| 12R22.5     | 18 | 152/149       | K            | 9.00         | 23.5             | 303                | 1100              | 3550          | 3250 | 930                | 930  |
| 315/80R22.5 | 20 | 157/154       | K            | 9.00         | 23.5             | 315                | 1096              | 4125          | 3750 | 900                | 900  |



**PATTERN**  
**LMT860**

| SIZE     | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|          |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 10.00R20 | 18 | 149/146       | K            | 7.50         | 17               | 278                | 1065              | 3250          | 3000 | 930                | 930  |
| 11.00R20 | 18 | 152/149       | K            | 8.00         | 18.5             | 293                | 1096              | 3550          | 3250 | 930                | 930  |
| 12.00R20 | 18 | 154/151       | K            | 8.50         | 18.5             | 315                | 1136              | 3750          | 3450 | 930                | 930  |



**PATTERN**  
**LMT778**

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 8.25R16 | 16 | 128/124       | K            | 6.50H        | 16.5             | 235                | 865               | 1800          | 1600 | 770                | 770  |



**PATTERN**  
**LMT825**

| SIZE     | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|          |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 10.00R20 | 18 | 149/146       | K            | 7.50         | 17               | 278                | 1065              | 3250          | 3000 | 930                | 930  |
| 11.00R20 | 18 | 152/149       | K            | 8.00         | 16.5             | 293                | 1096              | 3550          | 3250 | 930                | 930  |
| 12.00R20 | 18 | 154/151       | K            | 8.50         | 18.5             | 315                | 1136              | 3750          | 3450 | 930                | 930  |



**PATTERN**  
**LMT138**

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 7.50R16 | 14 | 122/118       | K            | 6.00G        | 15               | 215                | 815               | 1500          | 1320 | 770                | 770  |
| 8.25R16 | 16 | 128/124       | K            | 6.50H        | 15.5             | 235                | 865               | 1800          | 1600 | 770                | 770  |



**PATTERN**  
**LMT820**

| SIZE     | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|          |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 9.00R20  | 16 | 144/142       | K            | 7.00         | 16.5             | 259                | 1019              | 2800          | 2650 | 900                | 900  |
| 10.00R20 | 18 | 149/146       | K            | 7.50         | 17.5             | 278                | 1054              | 3250          | 3000 | 930                | 930  |
| 11.00R20 | 18 | 152/149       | K            | 8.00         | 18.5             | 293                | 1085              | 3550          | 3250 | 930                | 930  |
| 12.00R20 | 18 | 154/151       | K            | 8.50         | 18.5             | 315                | 1125              | 3750          | 3450 | 830                | 830  |



**PATTERN**  
**LMT737 ON/OFF ROAD**

| SIZE     | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|          |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5  | 18 | 152/149       | J            | 9.00         | 23               | 300                | 1085              | 3550          | 3250 | 930                | 930  |
| 12.00R20 | 18 | 154/151       | G            | 8.50         | 20               | 315                | 1125              | 3750          | 3450 | 830                | 830  |



## PATTERN LMT62

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 315/80R22.5 | 20 | 157/154       | K            | 9.00         | 22               | 300                | 1096              | 3550          | 3150 | 850                | 850  |



## PATTERN LMT72

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | J            | 9.00         | 24               | 297                | 1100              | 3550          | 3250 | 930                | 930  |



## PATTERN LM08

| SIZE             | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|------------------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|                  |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 11R22.5          | 16 | 148/145       | K            | 8.25         | 24               | 279                | 1065              | 3150          | 2900 | 850                | 850  |
| 12R22.5          | 18 | 152/149       | J            | 9.00         | 24               | 297                | 1100              | 3550          | 3250 | 930                | 930  |
| 285R/22.5(LM08E) | 18 | 152/149       | J            | 9.00         | 18.5             | 298                | 1044              | 3550          | 3250 | 900                | 900  |
| 825R16           | 18 | 131/126       | K            | 6.50         | 18               | 230                | 863               | 1950          | 1700 | 830                | 830  |
| 12.00R24         | 20 | 160/157       | C            | 8.50         | 25               | 315                | 1226              | 4500          | 4125 | 900                | 900  |



## PATTERN LMT82

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | J            | 9.00         | 23               | 293                | 1100              | 3550          | 3250 | 930                | 930  |



## PATTERN LMT52

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 12R22.5 | 18 | 152/149       | J            | 9.00         | 25.5             | 300                | 1096              | 3550          | 3250 | 930                | 930  |



## PATTERN C233

| SIZE    | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|---------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|         |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 11R22.5 | 16 | 148/145       | J            | 8.25         | 23.5             | 282                | 1064              | 3150          | 2900 | 850                | 850  |



## PATTERN LMT822

| SIZE     | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|          |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 8.25R16  | 16 | 128/124       | J            | 6.50H        | 17               | 235                | 865               | 1800          | 1600 | 770                | 770  |
| 12.00R20 | 18 | 154/151       | F            | 8.50         | 22.5             | 315                | 1136              | 3750          | 3450 | 830                | 830  |



## PATTERN LMT938

| SIZE     | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|          |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 11.00R20 | 18 | 152/149       | D            | 8.00         | 25.5             | 293                | 1096              | 3550          | 3250 | 930                | 930  |
| 12.00R20 | 18 | 154/151       | E            | 8.50         | 26.5             | 315                | 1136              | 3750          | 3450 | 830                | 830  |



## PATTERN LMT733

| SIZE        | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|-------------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|             |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 7.00R16     | 14 | 118/114       | J            | 5.50F        | 17               | 200                | 775               | 1320          | 1180 | 770                | 770  |
| 7.50R16     | 14 | 122/118       | K            | 6.00G        | 16.5             | 215                | 815               | 1500          | 1320 | 770                | 770  |
| 8.25R16     | 16 | 128/124       | K            | 6.50H        | 17               | 235                | 865               | 1800          | 1600 | 770                | 770  |
| 295/80R22.5 | 18 | 152/148       | M            | 9.00         | 20.5             | 298                | 1050              | 3550          | 3150 | 830                | 830  |
| 12.00R20    | 20 | 154/151       | G            | 8.50         | 24.5             | 315                | 1125              | 3750          | 3450 | 830                | 830  |



## PATTERN LMT932

| SIZE     | PR | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |      |
|----------|----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------|
|          |    |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL |
| 11.00R20 | 18 | 152/149       | F            | 8.00         | 23.5             | 293                | 1096              | 3550          | 3250 | 930                | 930  |
| 12.00R20 | 18 | 154/151       | F            | 8.50         | 23.5             | 315                | 1136              | 3750          | 3450 | 830                | 830  |



## PATTERN LMT732

| SIZE     | PR  | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |      | MAX PRESSURE (Kpa) |            |
|----------|-----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|------|--------------------|------------|
|          |     |               |              |              |                  |                    |                   | SINGLE        | DUAL | SINGLE             | DUAL       |
| 8.25R16  | 16  | 128/124       | G            | 6.50H        | 18               | 235                | 865               | 1800          | 1600 | 770                | 770        |
| 12.00R20 | 20  | 154/151       | F            | 8.50         | 26.5             | 315                | 1136              | 3750          | 3450 | 830                | 830        |
| 13.00R25 | *** | —             | —            | 10.00/1.5    | 27               | 350                | 1300              | 8500          | 4875 | 950/10km/h         | 700/50km/h |



## PATTERN LMT768

| SIZE     | PR  | LOADING INDEX | SPEED RATING | STANDARD RIM | TREAD DEPTH (mm) | SECTION WIDTH (mm) | OVERALL DIA. (mm) | MAX LOAD (KG) |          | MAX PRESSURE (Kpa) |          |
|----------|-----|---------------|--------------|--------------|------------------|--------------------|-------------------|---------------|----------|--------------------|----------|
|          |     |               |              |              |                  |                    |                   | SINGLE        | DUAL     | SINGLE             | DUAL     |
| 14.00R25 | *** | 169           | B            | 10.00/1.5    | 29               | 375                | 1370              | 5800          | —        | 700                | 700      |
| 13.00R25 | *** | —             | —            | 10.00/1.5    | 26.5             | 355                | 1304              | 4875          | 8500     | 700                | 950      |
|          |     |               |              |              |                  |                    |                   | (50km/h)      | (10km/h) | (50km/h)           | (10km/h) |